

**MATERIAL SAFETY DATA SHEET**  
**DT Super Glue Kicker**

**SECTION I PRODUCT IDENTIFICATION**

---

Printed 14/16/2005

Manufacturer: **Leather Magic Inc**  
**1610 Walkup Ave.**  
**Monroe, NC 28110**

---

**SECTION II HAZARDOUS INGREDIENTS**

---

**Health Ratings:** Health (NFPA): 2    Health (HMIS): 3    Flammability: 3    Reactivity: 0

<u>Ingredients</u>	<u>CAS#</u>	<u>Weight %</u>	<u>Exposure Limits</u>	<u>VP</u>	<u>HAP</u>
Acetone	67-54-1	90-98	750 ppm	NE	NO
N,N-dimethyl-p-toluidine	99-97-8	0-10	None	NO	NO

\*-> These items are listed on the SARA TITLE III Section 313 inventory

---

**SECTION III PHYSICAL DATA**

---

**Boiling Range:** 57 71 111 C / 133 160 232 F  
**Vapor Density:** heavier than air  
**Viscosity:** 1.0-2.0 CPS  
**Evaporation Rate:** Slower than Ether  
**Volatile Organics:** 6.6Lb/G  
**Solubility in Water:** Soluble  
**Appearance:** Liquid Water-White

**Ph:** N/A  
**Water Absorption:** Appreciable  
**Odor:** Sharp, Ketone like odor  
**Liquid Density:** Lighter than water  
**Weight/Gallon:** 6.89 Pounds  
**Specific Gravity:** 0.8

---

**SECTION IV FIRE AND EXPLOSION HAZARD DATA**

---

**Flammability Class:** CLASS 1B    **Flash point:** -16 C / 2 F    **LEL:** 2.6%    **UEL:** 12.8%

**-Extinguishing Media:** NFPA Class B extinguishers (Carbon Dioxide or Foam) for Class 1B liquid fires

**-Special Firefighting Procedures:** Water spray may be ineffective on fire but can protect fire-fighters & cool closed containers. Use fog nozzels if water is used.

Do not enter confined fire-space without full bunker gear (Helmet with face shield, bunker coats, gloves & rubber boots.

Use NIOSH approved positive-pressure self contained breathing apparatus.

**-Unusual Fire & Explosion Hazards: EXTREMELY FLAMMABLE!! VAPORS CAN CAUSE FLASH FIRE.**

Keep container tightly closed. Isolate from oxidizers, heat, sparks, electrical equipment & open flame. Closed containers may explode if exposed to extreme heat. Applying to hot surfaces requires special precautions. Empty container very hazardous! Continue all label precautions.

---

## SECTION V HEALTH HAZARD DATA

---

**-Permissible Exposure Level:** 200 ppm(skin)

**-Effects Of Overexposure:**

**Primary routes of entry:** (X) Skin Contact, (X) Eye Contact, (X) Inhalation (X) Ingestion

**Acute Hazards: Eye & Skin Contact:** Primary irritation to skin, defatting, dermatitis. Absorption through skin increases exposure. Primary irritation to eyes, redness, tearing, blurred vision. Liquid can cause eye irritation. Wash thoroughly after handling. **Inhalation:** Anesthetic. Irritates respiratory tract. Acute overexposure can cause serious nervous system depression. Vapor harmful. Breathing vapor can cause irritation. Acute overexposure can cause damage to kidneys, blood, nerves, liver & lungs. Repeated exposure over TLV can cause blindness. **Ingestion:** Can be fatal or cause blindness if swallowed. Cannot be made non-poisonous. POISON! Can cause irreversible nervous system damage & death. Harmful or fatal if swallowed. Swallowing can cause abdominal irritation, nausea, vomiting & diarrhea.

**Chronic Hazards: CANCER, REPRODUCTIVE & OTHER CHRONIC HAZARDS:** This product has no carcinogens listed by IARC, NTP, NIOSH, OSHA or ACGIH as of this date, greater or equal to 0.1%. This product may contain less than 142 ppm of Benzene. Not considered hazardous in such low concentrations. Absorption through skin may be harmful. Studies with laboratory animals indicate this product can cause damage to fetus.

**Medical Conditions Aggravated by Exposure:** Chronic overexposure can cause damage to kidneys, blood, nerves, liver & lungs. Persons with severe skin, liver or kidney problems should avoid use.

**Emergency Procedures:** Remove contaminated clothing and wash contaminated areas with plenty of water.

**-FIRST AID: Inhalation:** After high vapor exposure, remove to fresh air. If breathing is difficult, give oxygen. If breathing has stopped, give artificial respiration. CALL A PHYSICIAN IMMEDIATELY!

**Skin Contact:** Immediately remove contaminated clothing. Wash with large amounts of soap & water. Wash contaminated clothing before reuse. Discard contaminated shoes. If irritation persists, see physician.

**Eye Contact:** Flush with large amounts of water for 15 minutes. Get medical attention.

**Ingestion:** Induce vomiting promptly using physicians instructions or by having patient stick finger down throat. After vomiting has been induced, give two teaspoonful of baking soda in a glass of water. Call a physician. Never give anything by mouth to an unconscious person. Have patient lie down & keep warm. Cover eyes to exclude light.

---

## SECTION VI REACTIVITY DATA

---

**STABILITY:** ( ) Unstable, (X) Stable

**HAZARDOUS POLYMERIZATION:** ( ) May occur, (X) Will not occur

**INCOMPATIBILITY:** strong oxidizers, acids, Alkaline materials

**CONDITIONS TO AVOID:** Isolate from oxidizers, heat, sparks, electrical equipment & open flame

**MATERIALS TO AVOID:** Isolate from strong oxidizers such as permanganates, chromates & peroxides

**HAZARDOUS DECOMPOSITION PRODUCTS:** Carbon Monoxide, Carbon Dioxide, Nitrogen Oxides and others.

---

## SECTION VII SPILL OR LEAK PROCEDURES

---

**-STEPS TO BE TAKEN IN CASE MATERIAL RELEASED OR SPILLED:** Confine as much as possible. Dike and absorb with inert material such as vermiculite. Transfer to containers for disposal. Mop up area. Persons without proper protection should be kept from area until cleaned up.

**-WASTE DISPOSAL METHOD:** Recycle or dispose of waste in accordance with all Federal, state, and Local ordinances.

**Other Precautions:** Vapors may ignite explosively & spread long distances. Prevent vapor buildup. Put out pilot lights & turn off heaters, electrical equipment & other ignition sources during use & until vapors are gone.

---

## SECTION VIII SPECIAL PROTECTION INFORMATION

---

### **-PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING:**

Wear gloves, goggles and protective clothing to prevent contact with product. Wash clothing before reuse. Ventilate to keep vapors of this material below 60 ppm. If over TLV, in accordance with 29 CFR 1910.134, use NIOSH approved positive pressure self-contained breathing apparatus. Consult Safety Equipment Supplier. Use explosion-proof equipment. **Ventilation:** Local Exhaust.  
Store material at temperatures between 49 -C/120-F and 2 C/36-F. Do not store containers in direct sunlight.

---

## SECTION IX SPECIAL PRECAUTIONS

---

### **-SHIPPING INFORMATION: DOT SHIPPING NAME: NA**

**DOT Shipping Name:** Paint Related Material 3, UN1263 PG II

**DOT LABELS REQUIRED:** (FLAMMABLE LIQUID)

**FREIGHT DESCRIPTION:** Paint Related Material 3, UN1263 PG II

Empty containers should be reconditioned by certified firms (drums, pails). Sale of empty containers should be in accordance with applicable laws and regulations

**-OTHER PRECAUTIONS:** For industrial or professional use only. Do not get in eyes, on skin or clothing. Avoid contact with mouth. Avoid breathing vapor. Use only in areas adequately ventilated with enough air movement to remove vapors and prevent vapor buildup. Provide local exhaust ventilation if necessary to keep vapor level below recommended exposure limits. Utilize personal protective equipment when handling this product, i.e. impervious gloves (do not wear cotton gloves) and chemical goggles or safety glasses, whichever is most appropriate in the work situation. Keep container closed when not in use. Keep out of reach of children. Neither this data sheet or any statement contained herein grants or extends any license, expressly implied, in connection with patents issued or pending which may be the property of the manufacturer or others. The information in this data sheet has been assembled by the manufacturer based on its own studies and the work of others. The manufacturer makes no warranties, express or implied, as to the accuracy, completeness, or adequacy of the information contained herein. The manufacturer shall not be liable (regardless of fault) to the vendee, the vendee's employees, or anyone for any direct special or consequential damages arising out of or in connection with the accuracy, completeness, adequacy, or furnishing of such information.

**EFFECTIVE JANUARY 1, 1989:** Anyone selling or distributing a mixture or trade name product containing a toxic chemical (i.e., a chemical or member of chemical category in 40 CFR Part 372) must provide written notice to the recipient with the first shipment in each calendar year. This is pursuant to these legal requirements. Please note that if you are repackage or otherwise redistribute this product, a notice including the SARA 310 information should be sent to the recipients. If you are unsure of what you must report or require more information, call the EPA Emergency Planning and Community Right to Know Hotline: (800) 535-0202 or (202) 479-2449.

MSDS's are an important part of employee hazard communication information and training programs required of employers under the OSHA hazard Communication Standard. (29 CFR 1910.1200).